



- Non waterproof
- Resolution: 0.01mm/0.0005"
- Button function: on/off, zero, mm/inch, ABS, data preset
- Battery CR2032
- Made of stainless steel



1136-501



With data interface  
(data output cable code 7315-22 , 7302-22 ,  
optional, for calipers with c=24mm or 31mm)

(mm)

| Code      | Range          | Accuracy | a  | b  | c  | d   | L    |
|-----------|----------------|----------|----|----|----|-----|------|
| 1136-301  | 0-300mm/0-12"  | ±0.05mm  | 18 | 45 | 24 | 100 | 420  |
| 1136-451  | 0-450mm/0-18"  | ±0.05mm  | 18 | 45 | 24 | 100 | 625  |
| 1136-501  | 0-500mm/0-20"  | ±0.05mm  | 18 | 45 | 24 | 100 | 675  |
| 1136-502  | 0-500mm/0-20"  | ±0.06mm  | 18 | 45 | 24 | 150 | 675  |
| 1136-503  | 0-500mm/0-20"  | ±0.06mm  | 24 | 60 | 31 | 200 | 675  |
| 1136-601  | 0-600mm/0-24"  | ±0.05mm  | 18 | 45 | 24 | 100 | 770  |
| 1136-1002 | 0-1000mm/0-40" | ±0.08mm  | 24 | 60 | 31 | 150 | 1220 |
| 1136-1502 | 0-1500mm/0-60" | ±0.11mm  | 24 | 60 | 42 | 150 | 1780 |
| 1136-2002 | 0-2000mm/0-80" | ±0.14mm  | 24 | 60 | 42 | 150 | 2290 |

Built-in wireless

(receiver code 7315-2/3/6/7/8/9 is required)

(mm)

| Code       | Range         | Accuracy | a  | b  | c  | d   | L   |
|------------|---------------|----------|----|----|----|-----|-----|
| 1136-301WL | 0-300mm/0-12" | ±0.05mm  | 18 | 45 | 24 | 100 | 420 |
| 1136-451WL | 0-450mm/0-18" | ±0.05mm  | 18 | 45 | 24 | 100 | 625 |
| 1136-501WL | 0-500mm/0-20" | ±0.05mm  | 18 | 45 | 24 | 100 | 675 |
| 1136-502WL | 0-500mm/0-20" | ±0.06mm  | 18 | 45 | 24 | 150 | 675 |
| 1136-601WL | 0-600mm/0-24" | ±0.05mm  | 18 | 45 | 24 | 100 | 770 |