

Leakage Current Clamp Meters

Clamp Leaker

Model: 140



Features

Model	140
Display	4 digits LCD: 32x15mm
Data storage	60 groups
Clamp size	φ40mm
Sampling rate	2 times/s
Data hold	√
Over range indication	√
Auto off	Idle for 5 minutes
Low battery indication	√
Rated power	5mW
Working condition	-0°C ~ 40°C, below 80%RH
Storage condition	-10°C ~ 60°C, below 70%RH
Insulations	AC2kV/rms (between core and box)
Safety	IEC1010-1, IEC1010-2-032, pollution grade: 2, CAT III(600V)

Specifications

Model	140
Function	AC leakage current AC current
Range	0.00 ~ 300.0A (50/60Hz)
Resolution	0.01mA
Measuring Range	30mA/300mA, 30A/300A
Accuracy (at 23°C±1°C, <70%RH)	0.00mA ~ 9.99mA: ±1.2%±5
	10.0mA ~ 300.0mA: ±1.5%±5
	0.00A ~ 9.99A: ±1.2%±5
	10.0A ~ 99.9A: ±1.5%±5

General Information

Model	140
Power Supply	Button Cell LR-44×2 or SR-44×2
Product Size	64mm×160mm×23mm
Product Weight	120g
Standard Accessories	Manual, battery, pouch