

Force Gauge

Digital Force Gauges

Model: 2N 3N 5N 10N 20N 30N 50N 100N 200N 300N 500N



Features

| Model | 2N 3N 5N 10N 20N 30N 50N 100N 200N 300N 500N |
|---------------------------------|--|
| Gravity acceleration setting | √ (default value 9.800) |
| Backlight | √ |
| Zero function | √ |
| Peak hold | √ |
| Alarm for upper and lower value | √ |
| Low battery indication | √ |
| Units selectable | N/Kg/Lb |
| Auto off | 10 minutes idle |

Specifications

| Model | 2 | 3 | 5 | 10 | 20 | 30 | 50 | 100 | 200 | 300 | 500 |
|-----------------|-------------------------------|-----------------|----------------|-----------------------------|--------------|--------------|-------------|--------------------------|--------------|--------------|---------------|
| | 2N | 3N | 50N | 10N | 20N | 30N | 50N | 100N | 200N | 300N | 500N |
| Max. Load value | 0.2kg 0.45Lb | 0.3kg 0.65Lb | 0.5kg 1.1Lb | 1kg 2.2Lb | 2kg 4.5Lb | 3kg 6.5Lb | 5kg 11Lb | 10kg 22Lb | 20kg 45Lb | 30kg 65Lb | 50kg 110Lb |
| Resolution | 0.001N 0.0001KG 0.001Lb | | | 0.01N 0.001KG 0.001Lb | | | | 0.1N 0.01KG 0.01Lb | | | |
| Accuracy | ±0.5% | | | | | | | | | | |

General Information

| Model | 2N | 3N | 5N | 10N | 20N | 30N | 50N | 100N | 200N | 300N | 500N |
|----------------------|--|----|----|-----|-----|-----|-----|------|------|------|------|
| Power Supply | 3.7V Rechargeable lithium battery Charging time: 4-6hours Battery life: ≥ 300 times Input:AC100- 240V 50-60Hz Output: DC 5V 1000mA | | | | | | | | | | |
| Product Size | 140mmx71mmx35mm | | | | | | | | | | |
| Product Weight | 300g | | | | | | | | | | |
| Standard Accessories | Chargerx1, Clampx4, Extension Tube x 1, Mounting Screw x4, Manualx1 | | | | | | | | | | |