

Digital Insulation Resistance Testers  
Model: 60B+ 60D+ (2022 version)



HD large screen  
Large-screen LCD display,  
clear digital symbol display,  
easy to read



Test button ▶  
Press this button to start a  
measurement; you can also  
long press the button to lock it  
for continuous measurement

**Features**

Model	60B+	60D+
Low Battery Indication	√	√
Backlight display	√	√
Alarm function	√	√
Over load indication	√	√
Unit symbol display	√	√
Auto power off	√	√
Max. display	5000	2000
LCD size	85x60mm	
Operation condition	(0~40)°C, 30%RH~85%RH	
Input Impedance	1MΩ	
Frequency Response	(50-200) Hz	

**Specifications**

Rated voltage	60B+	60D+
250V	0.400MΩ—1.999MΩ	
	2.00MΩ—19.99MΩ	
	20.0MΩ—199.9MΩ	---
	0.200GΩ—0.999GΩ	
500V	0.600MΩ—1.999MΩ	0.600MΩ—1.999MΩ
	2.00MΩ—19.99MΩ	2.00MΩ—19.99MΩ
	20.0MΩ—199.9MΩ	20.0MΩ—199.9MΩ
	0.200GΩ—1.99GΩ	0.200GΩ—1.99GΩ
1000V	---	2.00GΩ ~ 4.99GΩ
	0.800MΩ—1.999MΩ	1.000MΩ—1.999MΩ
	2.00MΩ—19.99MΩ	2.00MΩ—19.99MΩ
	20.0MΩ—199.9MΩ	20.0MΩ—199.9MΩ
2500V	0.200GΩ—4.99GΩ	0.200GΩ—1.999GΩ
	---	2.00GΩ—9.99GΩ
		3.00MΩ-19.99MΩ
		20.0MΩ-199.9MΩ
Resistance accuracy		0.200GΩ-1.999GΩ
		2.00GΩ-19.90GΩ
		20.0GΩ-49.9GΩ
ACV: 20-1000V	± (2%+3)	± (2%+3)
DCV:±(20 ~ 1500)V	± (2%+3)	± (2%+3)

**General Information**

Model	60B+	60D+
Power Supply	8x1.5V AA batteries	AC adapter (not included)
Product color	Black + orange	
Product weight	178×110×59mm	
Product size	600g	
Standard accessories	Test leads / batteries / manual/ shoulder strap/ alligator clips	