

Digital Clamp Meter

Model: 615B



**Features**

Model	615B
Diode & continuity Test	√
Relative value measurement	√
Low battery indication	√
Data Hold	√
NCV (non-contact voltage detection)	√
Auto power off	√
Live wire test	√
Flash light	√
Zeroing	√
Low-Z measurement	√
V.F.C (low pass filter)	√
Inrush current measurement	√
DC current zeroing	√
Operation way	Auto range
Max. display	5999
Jaw size	40mm

**Specifications**

Function	Range	615B
DC V	600mV/6V/60V/600V/1500V	± (0.5%+7)
AC V	6V/60V/600V/1000V	± (1.0%+10)
Low-V(AC)	6V/60V/300V	± (1.0%+10)
DC A	60A/600A/1000A	± (4.0%+10)
AC A	60A/600A/1000A	± (4.0%+10)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/20MΩ/60MΩ	± (1.0%+5)
Capacitance	1nF/10nF/100nF/1μF/10μF/100μF/1mF/10mF	± (5.0%+10)
Frequency	10Hz-10MHz	± (0.3%+3)
Duty cycle	10.0%-90.0%	0.1%
Temperature	-20°C~1000°C / -4°F~1832°F	± (2.0%+5)

**General Information**

Model	615B
Power Supply	AAA,1.5Vx2
Product color	Black+ Orange
Product weight	313g
Product size	230x75x40mm
Standard accessories	Test leads, batteries, manual, pouch, temperature probe