

PH /TEMPERATURE PEN



8686



8684

8685



86851


Low Ionic Strength pH Pen

Ordering Code
 VZ8684AZ, 8684 pH pen
 VZ8685AZ, 8685 pH pen
 VZ8686AZ, 8686 pH pen
 VZ86851AZ, 86851 low ionic strength pH pen

*Available for EB project

IP65 pH pen/Low Ionic Strength pH Pen 8684/8685/8686/86851

- Big LCD with dual display
- pH/ Temperature dual display
- Measuring stability indicator
- One touch auto-calibration up to 3 points
- Calibration values are adjustable
- Cap to keep sensor wet & last life time
- Perfect for well water, surface water, lake water, treated effluent water and boiler feed water (86851 only)



NEW DESIGN
PROTECTION BOTTLE

Model	8684	8685/86851	8686
pH range	2.0~12.0	0.0~14.0	0.00~14.00
pH accuracy	+/-0.3	+/-0.2	+/-0.05
pH resolution	0.1	0.1	0.01
Temp. range	N/A	0~60.0°C	0~60.0°C
Temp. accuracy	N/A	+/-1°C	+/-0.5°C
Temp. resolution	N/A	0.5	0.1
ATC	N/A	ATC	ATC
LCD size	30(H)x18(W)mm		
Operating temp.	0~50°C		
Operating RH%	Humidity<80%		
Storage temp.	-10~50°C		
Storage RH%	Humidity < 90%		
Sensor life time	>6 months (with good maintenance)		
Dimension	165(L)x35(W)x32(H)mm		
Weight	115g		
Battery	LR44 x 4pcs		
Optional	N/A		
Standard Package	Meter/Battery/Manual/Paper box		

Install the battery with correct polarity:

