




8692

IP65 Long Tube pH pen/Low Ionic Strength pH Pen 8691/8692/86921

- 12cm long pH probe
- Big LCD with dual display: pH & Temperature
- Perfect low cost pH pen to measure pH value in below water body: well water, surface water, lake water, treated effluent water and boiler feed water (86921 only)
- One touch auto-calibration up to 3 points
- Calibration values are adjustable
- Storage bottle to keep sensor wet & last life time



Auto Power Off



Auto Temp. Compensation



Metric/Imperial



Low Battery




HOLD



IP65

Storage Buffer Bottle



Low Ionic Strength pH Pen



86921

Model	8691	8692 / 86921
pH range	0.00~14.00	0.00~14.00
pH accuracy	+/-0.2	+/-0.1
pH resolution	0.01	0.01
Temp. range	N/A	0~60.0°C
Temp. accuracy	N/A	+/-1°C
Temp. resolution	N/A	0.5°C
ATC	N/A	ATC
LCD size	29(H)x22.5(W)mm	
Operating temp.	0~50°C	
Operating RH%	Humidity<80%	
Storage temp.	-10~50°C	
Storage RH%	Humidity < 90%	
Sensor life time	>6 months (with good maintenance)	
Dimension	226(L)x36(W)x20(H)mm	
Weight	115g	
Battery	CR2032 x 2pcs	
Optional	N/A	
Standard Package	Meter/Battery/Manual/Paper box	

86921 is perfect for well water, surface water, lake water, treated effluent water and boiler feed water



Ordering Code

VZ8691AZ, 8691 long tube pH pen
VZ8692AZ, 8692 long tube pH pen
VZ86921AZ, 86921 low ionic pH pen

*Available for EB project

Designed for testing sample container with limited opening size:

