

**Leakage Current Clamp Meters**

High /Low Voltage Leakage Clamp Meter

Model: 9000 9000B



**Features**

Model	9000/9000B
Data storage	99 Groups
Peak hold	√
Date hold	√
Overflow indication	√
Auto power off	√
Clamp size	φ48mm
Display	4 digits LCD ,47*28.5mm
Backlight	√
Low battery indication	√
Insulation	AC 100kV/rms (Between the 5th insulation rod and the clamp center)
Working condition	(-25 ~ 40)°C, below 80%Rh
Storage condition	(-10 ~ 60)°C, below 70%Rh

**Specification**

Model	9000	9000B
Function	High/Low voltage AC current	High/Low voltage AC current
Transmission distance	N/A	Max. distance 30m
Measuring range	0.00mA ~ 1200A (50/60Hz automatic)	0.00mA ~ 1200A (50/60Hz automatic)
Resolution	1mA	1mA
Accuracy	0.00mA~299mA: ±1%±3	0.00mA~299mA: ±1%±3
	0.30A~9.99A: ±1.5%±5	0.30A~9.99A: ±1.5%±5
	10.0A~199.9A: ±2%±5	10.0A~199.9A: ±2%±5
	200A~399A: ±2.5%±5	200A~399A: ±2.5%±5
	400A~600A : ±3%± 5	400A~600A : ±3%± 5
Sampling speed	2 times/s	2 times/s
	Live voltage	Under 60KV insulated wire test (Test with insulation rod), Under 35kV bare wire

**General Information**

Model	9000	9000B
Power supply	1.5V AAA*4	Main Unit:1.5V AAA*4 Clamp: 1.5V AAA*4
Product size	76mmx255mmx31mm	Main Unit:78mm×165mm×42mm Clamp : 76mm×255mm×31mm
Product weight	3450g	Main Unit:330g Clamp: 335g
Insulation rod size	φ32mm,1m/pc x5pcs	φ32mm,1m/pc x5pcs
Standard accessories	Clamp x1, Insulation rod(1m) x5, batteries, manual, pouch	Receiver x1, Clamp x1, Insulation rod(1m) x5, battery, manual, pouch